



Specifications

Electrical
 Voltage Rating: 100V(AC)
 Current Rating: 2A
 Contact Resistance: 20mΩ max.
 Dielectric Withstandeing Voltage: 800V AC/1min.
 Insulation Resistance: 1000mΩ min.

Material
 Circuits: 2~16
 Insulator: Nylon 66 UL 94V-0
 Color: White or Natural
 Contact: Brass 0.50mm(0.20") Square Pin
 Plating: Tin or Gold Plated
 Temperature Range: -25° C ~ +85° C
 Applicable PC Board Thickness: 0.8 to 1.6mm

Poles	Dimension mm (in.)	
	A	B
2	2.0(0.079)	6.1(0.240)
3	4.0(0.157)	8.1(0.318)
4	6.0(0.236)	10.1(0.397)
5	8.0(0.315)	12.1(0.476)
6	10.0(0.394)	14.1(0.555)
7	12.0(0.472)	16.1(0.634)
8	14.0(0.551)	18.1(0.713)
9	16.0(0.630)	20.1(0.791)
10	18.0(0.709)	22.1(0.870)
11	20.0(0.787)	24.1(0.949)
12	22.0(0.886)	26.1(1.028)
13	24.0(0.945)	28.1(1.106)
14	26.0(1.024)	30.1(1.185)
15	28.0(1.102)	32.1(1.263)
16	30.0(1.181)	34.1(1.343)

RoHS Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD.		TOLERANCE .0 ±0.3 .00 ±0.2 .000 ±0.1 ANG. ±3°	PART NAME 品名
DWG. Karen	SCALE 參考	UNIT M M	2.0mm WAFER STRAIGHT TYPE 1*XXP WHITE COLOR ROHS
DATE 2013/07/15	PAGE 1 OF 1	SIZE A 4	PART NO. 料號 W2103-XXPSSXXWR